

assembly having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, means deployed between said cylinder assembly and said component assembly to cause said component assembly and said second surface to rotate while reciprocating relative to said cylinder assembly and said first surface, said component assembly being linked to said shaft by said mechanism, said mechanism causing said shaft to only rotate while said component assembly reciprocates and rotates.

219. *(Amended)* A device for the working of fluids, said device comprising a housing, a cylinder assembly, at least one component assembly mounted to reciprocate within said cylinder assembly, said cylinder assembly having at least one first working surface and said component assembly having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, means deployed between said cylinder assembly and said component assembly to cause said component assembly and said second surface to rotate while reciprocating relative to said cylinder assembly and said first surface, said cylinder assembly being rotatably mounted within said housing.

220. *(Amended)* A device for the working of fluids, said device comprising a cylinder assembly, at least one component assembly mounted to reciprocate

within said cylinder assembly, said cylinder assembly having at least one first working surface and said component assembly having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, each of said surfaces being of endless wave-like configuration to permit and limit said component assembly and said second surface to both reciprocate and rotate relative to said cylinder assembly and said first surface.